

Stadium

LED Floodlight 200W / 4000 K / 24000 lm

Stadium floodlight combines performance and high quality LED modules with a straightforward yet elegant design, providing high performance features to adequately and ideally cover all areas. Stadium floodlight is designed to bright large indoor and outdoor spaces with high intensity, wide-area coverage, and low energy consumption.



Product data

General information

Dimensions (mm)	470 (L) x 385 (W) x 51 (H)
Materials	Body: Powdercoated Aluminium Diffuser: Glass
Finish	Gray (RAL 9004)
Product Weight (Kg)	5.35 Kg ± 30g
Ingress Protection	IP65
Impact Rating (IK)	06
Article no.	PECLST4K6D200

Supply & power information

Input Voltage & Frequency (V~ / Hz)	220-240V - 50/60 Hz
Safety Class	I
Circuit Wattage (W)	200 W
LED Wattage (W)	200 W
Input Current (mA)	0.72 mA
Inrush Current/Time	100A (500μS)
Power Factor	>0.9
Operating Temperature (°C)	-20°C to +45°C
Critical Temperature (°C)	+60
Input Mains Cable	3 x 1mm ² H05-RNF (2 metre)

Dimming Information

Dimmable	No
Dimming Format	Non-Dimmable

Certificates & Standards

Standards	CE, Cmm, Rohs,
-----------	----------------


Luminaire Output

Colour Temperature (K)	4000K
Luminous flux	24000 lm
Efficacy (lm/W)	120 lm/W ±10%
Colour Render Index (CRI)	≥80
Beam Angle (°)	60°
LED Lifetime (Hours)	50,000 H

Dimensions & Weight

Length	470 mm
Width	385 mm
Height	51 mm
Product Weight	5.35 Kg
Cable Length	50,000

Dimensional drawing



LED Floodlight Stadium 200W / 4000 K / 24000 lm